

Specifications

Weights, Dimensions, Electrical Specifications

Patient Weight (<i>maximum</i>):	450 lbs (204.1 kg)
Paper Roll (<i>maximum size</i>):	18 in. long x 3.5 in. diameter (45.7 x 8.9 cm)
Range of Motion & Dimensions:	[See Range of Motion & Dimensions page]
Weight of Table: 630 (w/standard base) w/packaging & skid 630 (w/rotational base) w/packaging & skid	455 lbs (206.4 kg) 510 lbs (231.3 kg) 540 lbs (244.9 kg) 600 lbs (271.1 kg)
Power Cord:	8 ft. (243.8 cm) long
Electrical Requirements:	[See Model I.D. / Compliance Charts]
Foot / Hand Control Voltage:	10 VAC, SELV (Safety Extra Low Voltage)
Duplex Receptacle (optional) maximum load:	115 VAC, 3A, 50/60 Hz
Fuses: <i>Located at power cord inlet:</i> F1 & F2	6.3 A, 250V, Type T, 5 x 20 mm
Duty Cycle (motor run time):	Intermittent Operation [30 seconds ON / 5 minutes OFF]
Classifications:	Class 1, Type B Applied Part
Protection against ingress of fluids: <i>Foot Control <u>only</u>:</i>	Ordinary Equipment IPX1
Regulatory Compliance:	[See Compliance Charts]



WARNING

Equipment not suitable for use in the presence of a flammable anesthetic mixture.