

Specifications

Weights & Electrical Specifications

Patient Weight <i>(maximum)</i>	400 lbs (181.4 kg)
Paper Roll <i>(maximum size)</i>	<i>(See Paper Roll & Tear Strap page)</i>
Range of Motion & Dimensions	<i>(See Range of Motion & Dimensions page)</i>
Weight of Table <i>[Weights listed are for 115V models. The 230V transformer adds 14.5 lbs (6.5 kg)]</i>	
w/upholstery w/package & skid <i>(no upholstery)</i> Upholstery w/package <i>(shipped separately)</i>	325 lbs (147 kg) 375 lbs (192.7 kg) 40 lbs (18.1 kg)
Power Cord(s) <i>[115V models have two cords]</i>	8 ft. (243.8 cm) long
Electrical Requirements	<i>[See Compliance Chart]</i>
Foot Control Voltage	14 VAC, SELV (Safety Extra Low Voltage)
Duplex Receptacle <i>(maximum load)</i> <i>(not available on 230 volt models)</i>	115 VAC, 5A, 50/60 Hz
Fuses <u>222/223 (all)</u> F1 & F2 <i>(on main PC board)</i> F3 <i>(on main PC board)</i> F4 <i>(on main PC board)</i> 223 <i>(only)</i> F5 <i>(on main PC board)</i> <u>Models w/ drawer heater</u> distribution board fuses (2) <u>222 (-017)</u> located next to IEC inlet (2)	10A, 250V, Slo-Blo, 1/4" x 1 1/4" 5A, 250V, Slo-Blo, 1/4" x 1 1/4" 187 mA, 250V, Slo-Blo, 1/4" x 1 1/4" 4A, 250V, Slo-Blo, 1/4" x 1 1/4" 800 mA, 250V, Slo-Blo, 5 x 20 mm 4A, 250V, Slo-Blo, 5 x 20 mm
Duty Cycle (Motor Run Time) Receptacles / Drawer Heater	Intermittent Operation <i>[Domestic: 30 seconds ON / 5 minutes OFF]</i> <i>[Export: 25 seconds ON / 7 minutes OFF]</i> Continuous Operation
Classifications	Class I, Type B Applied Part Intermittent Operation <i>[Domestic: 30 seconds ON / 5 minutes OFF]</i> <i>[Export: 25 seconds ON / 7 minutes OFF]</i>
Protection against ingress of fluids	IPXO <i>[Foot Control only: IPX1]</i>